

BUILT-IN LOW-ACTION CONTACT TYPE M

TYPE M Hz

INSTRUMENT	: class 1
MINIMAL RANGE	: 1 bar
CONNECTOR	: cable junction box, SEE BELOW
HYSTERESIS	: max. 1% up and down
SETPOINT(S)	: from outside with key
WINDOW	: PMMA - plexiglass
POINTER	: black (adjustable see page 24)
CONTACT POINTER(S)	: red

ELECTRICAL SWITCH CAPACITY

AC	: 50 VA (max. 250V)
DC	: 30 W (max. 250V)



PBX100XA
+ M-12 Hz



CONTACT TYPE	SWITCH FUNCTION	CABLE JUNCTION BOX	CASE DIMENSIONS				
			100	160	96x96	144x144	72x144
M-1 Hz		<p>Hirschmann</p>					
M-2 Hz							
M-3 Hz							
M-11 Hz							
M-12 Hz							
M-21 Hz							
M-22 Hz							
M-xx Hz +GS	<p>example: S-21 Hz GS</p>	<p>Wiebrock</p>					
M-33 Hz							N.A.
M-33 Hz+GS							N.A.
M-xxx Hz	functions to be specified at order						N.A.
M-xxxx Hz	functions to be specified at order		O.D.	O.D.	O.D.	O.D.	N.A.
OPTION			EXTRA COSTS				
Lx	LIQUID FILLED CASE (ONDINA)				N.A.	N.A.	N.A.